EMI Reduction Oscillator

Features

- FCC approved method of EMI attenuation
- Proprietary "SaΦic™" technology
- Supply voltage 1.65V~1.95V
- Frequency range 1~125Mhz
- Output Multiple Deviation Selections
- Minimum frequency deviation selection capability
- Pin1 modes: Spread disable
- Package QFN:3.2x2.5mm

Applications

- SATA, Ethernet, PCI express, Video, Wireless
- Computing, Storage, Networking, Telecom, Industrial Control

Table1. Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit.	Condition
Output Frequency Range	F	1	100	125	MHz	V_{DD}=1.8V
Frequency Stability	F_stab	-20		+20	PPM	Inclusive of initial tolerance at 25 ºC， and variations over operating temperature, rated power supply voltage and load.
Operating Temperature Range	T_use	-40		+85	ºC	
Supply Volage	V_{DD}	1.65	1.8	1.95	V	
Current Consumption	I_{DD}	-		28	mA	No load condition, f=100MHz, V_{DD} =1.8V
OE mode disable current	I_od			18	mA	When OE=GND, output is Pulled Down
Duty Cycle	DC	45		55	%	Please refer figure 2
Rise/Fall Time	Tr, Tf		1.5		nS	15pF load, 10%~90% V_{DD}, high drive (V_{DD} =1.8V)
Output Voltage High	V_{OH}	V_{DD} -0.4	-	-	V_{DD}	I_{OH}=-4mA, I_{OL}=4mA, Standard Drive
Output Voltage Low	V_{OL}	-	-	0.4	V_{DD}	
Input Voltage High	V_{IH}	70%	-	-	V_{DD}	Pin1, OE
Input Volage Low	V_{IL}	-	-	30%	V_{DD}	Pin1, OE
Startup Time	T_start	-	5	7	mS	Measure from the time V_{DD} reaches its rated minimum value.
PK-PK Period Jitter	T_jitt	-	200	350	pS	F=100MHz, V_{DD} =1.8V
First year Aging	F_aging	-1.5		+1.5	PPM	25 ºC
10-year Aging		-5		+5	PPM	

Notice: The information in this document is subject to change without notice.

Table2. Pin Configuration

Pin	Symbol		Functionality
1	SSEN	Spread Disable	H: Spread = ON L: Spread = OFF
2	GND	Power	Electrical ground
3	OUT	Output	Oscillator output
4,5	V_{DD}	Power	Power supply voltage

TOP View



Table3. Deviation select Table

Deviation Select	2	4
Deviation	±0.44%	±0.25%

Notes: Please refer to ordering information for deviation select.

Test Circuit and Waveform



Figure 1. Test Circuit



Figure 2. Waveform

Notes: Duty Cycle is computed as Duty Cycle = TH/Period.

Notice: The information in this document is subject to change without notice.

Timing Diagram



T-start: Time to start from power-off

Figure 3. Startup Timing

Ordering Information



Marking



Temperature Grade	Temperature Range	Frequency Stability (PPM)
I	-40~85℃	±20

Notice: The information in this document is subject to change without notice.

Suggested reflow profile

Total time :600 sec. Max **Solder melting point:220℃**



Package Dimension



Top View

Side View



Bottom View



Suggested Layout

Units : mm

Notice: The information in this document is subject to change without notice.

evision History

Revision Number	Date of Release	Changes
1.0	12/01/2023	1)Preliminary datasheet
1.1	03/22/2024	Modify the marking

Notice: The information in this document is subject to change without notice.